

RENDER SELECTOR

The following tables have been designed to help you find the right base-coat for your particular substrate. Whilst multiple products can be used on many surfaces, we have suggested the ones that we feel will give you optimum results in terms of performance and workability.



Macrender®

COARSE

HBS

SUPASKIM

HI-BUILD

DRI-PATCH

COARSE FR

RIGID & POROUS SURFACES					
SUBSTRATE	MACRENDER®	COARSE	FR	SUPASKIM	HI-BUILD
Clay & concrete bricks and blocks with flush joints	+++	+++	+++	+	+
Clay & concrete bricks and blocks with raked joints	+	++	++		+++
Hebel Blocks & Power Panels	+	+	+++	+	+
Sponge finish over brick & blockwork	+			+++	

NON-POROUS SURFACES				
SUBSTRATE	MACRENDER® HBS	DRI-PATCH	MACPATCH COARSE	MACRENDER® MAC. COARSE HI-BUILD
Glazed brickwork	+++	++		+
Glazed brickwork with raked joints	++			+
Painted masonry surfaces - Smooth	++	+++	++	+
Painted masonry surfaces - Smooth	++	+++	+++	

NON-POROUS SURFACES				
SUBSTRATE	MACRENDER® HBS	DRI-PATCH	MACPATCH COARSE	MACRENDER® MAC. COARSE HI-BUILD
<i>Painted masonry surfaces - Rough</i>	+++	+		+
<i>EPS Expanded polystyrene base sheet</i>	+++	+		
<i>Concrete panels & formwork</i>	++	+++		+

FLEXIBLE SURFACES			
SUBSTRATA	MACRENDER® HBS	DRI-PATCH	MACPATCH COARSE
<i>EPS Expanded polystyrene base sheet</i>	+++	+	
<i>Fibre-cement sheet constructions</i>		++	+++
<i>AFS wall system</i>	+++	++	+
<i>Rediwall System</i>	+++	+	+
<i>Kooltherm K-Series</i>	+++		

+

Can be used

++

Recommended

+++

Highly recommended

+

Can be used when mixed with Macbond. See Macbond data for recommended ratios.

IMPORTANT NOTE:

Melbourne Acrylic Coatings Victoria Pty Ltd, its staff and distributors will not accept responsibility for any failure caused as a result of factors beyond our control including but not limited to onsite handling, preparation or application of this product. Application of this product should only be performed by qualified trades people trained in the use of this type of product. Information supplied in this publication is based on our testing and experience and is given in good faith. Suitability of this product should be independently determined prior to use. Warranty is limited to the replacement of any materials proven to be faulty. MAC will not warrant job defects caused as a result of but not limited to, structural movement or entrapped moisture.

WWW.MELBACRYLIC.COM.AU

